

(19) World Intellectual Property  
Organization  
International Bureau



541666

(43) International Publication Date  
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number  
**WO 2004/064091 A1**

(51) International Patent Classification<sup>7</sup>: **H01G 9/00**

(21) International Application Number:  
PCT/NL2003/000013

(22) International Filing Date: 9 January 2003 (09.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **MOLECULAR BIOPHYSICS INC.** [NL/NL]; c/o Ardyth Eisenberg, 7320 Lake Street, Unit 5, River Forest, IL 60305-2231 (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **EISENBERG, Robert, Shlm** [US/US]; 7320 Lake Street, Unit 5, River Forest, IL 60305-2231 (US).

(74) Agent: **PRINS, A., W.**; Nieuwe Parklaan 97, NL-2587 BN Den Haag (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: LIQUID BASED ELECTRONIC DEVICE



(57) Abstract: An electronic device, comprising: at least one channel with a fluid fillable channel interior and an electrically insulating wall surrounding at least partially the channel interior, which channel interior, in use, contains charge carriers, which electronic device further comprises: at least one control electrode, which electrode is electrically isolated from the channel interior and in capacitive contact with the channel interior. Furthermore, methods for use of such an electronic device, for example mixing or separating fluids.